SULFABATE NGL

PRODUCT DATA SHEET

PRODUCT: SULFABATE NGL

SERIES 100
CATALYST

MODIFIED FROM THE FLAGSHIP H2SZERO PRODUCT WITH DIFFERENT PRODUCTION TOLERANCES SUITED SPECIFICALLY TO THE STRINGENT REQUIREMENTS OF PURIFYING NATURAL GAS LIQUID (NGL) STREAMS.

A LOW SURFACE AREA HIGH STRENGTH MIXED METAL OXIDE EXTRUDED SCAVENGER MEDIA FOR TREATING NGLS NEEDING TO PASS THE COPPER STRIP TEST

TYPICAL PROPERTIES:

APPEARANCE: BROWN COLORATION
FORM: TRI-LOBE EXTRUDATE
LOADING DENSITY: TYPICALLY 50 - 55 LBS./FT
LOADING METHOD: DUMP OR SOCK LOADING
BULK CRUSHING STRENGTH: < 0.1 WT.%
HANDLING ATTRITION: < 0.01 WT.%
OPERATING TEMPATURE RANGE: 20 TO 100 DEGREES FARENHEIGHT
PACKAGING: 2,000 LB. SAFETY ENHANCED SUPER SACKS

H2S ZERO
GAS & NGL SOLUTIONS
14724 LONESTAR RD
SAPULPA, OK 74066
877.918.ZERO (9376)